

150 series stepper motor driven peristaltic pump for liquids

Specification Sheet 1 (last updated Jul 2011)

Panel mounted Bipolar Stepper Motor, oem peristaltic pumps for accurate dispense of liquids, from 0.2ml/min to 270ml/min. Our USB stepper controller is best suitable for this pump.



- Easy tube replacement
- Continuous or fixed tube length
- Accurate dispense
- 3 roller system
- Choice of 3 tube diameters
- Suitable for continuous operation
- Panel mounting
- No lubrication
- Self priming
- CE marked


Stepper Motor:	24V DC
Current max.....	2.5A
Max ambient operational temperature.....	50°C
Material wetted parts.....	Santoprene or Silicone
Max pressure.....	1 bar
Weight	227g
Life expectancy.....	>1000 hours
Max speed using Uno controller.....	2600steps/sec(780rpm)
Steps per rev.....	200

Use the following data to calculate your requested rotor speed:

Flow per 360° rotor revolution

ID Ø1.0mm tube.....	48µl
ID Ø2.0mm tube.....	160µl
ID Ø3.0mm tube.....	345µl


i.e. Speed 2600steps/sec = $2600/200*60*0.345=269.10\text{ml/min}$



The Williamson Manufacturing Company Ltd provides no warranty on usage of pumps. We recommend that life tests be carried out prior to use. This information is given in good faith and believed to be correct and current at time of publishing. The Williamson Manufacturing Company Ltd cannot accept responsibility for its inaccuracy or any errors or omissions contained herein. Copyright The Williamson Manufacturing Company Ltd 2008

150 series stepper motor driven peristaltic pump for liquids

Specification Sheet 2 (last updated Jul 2011)



The Williamson Manufacturing Company Ltd provides no warranty on usage of pumps. We recommend that life tests be carried out prior to use. This information is given in good faith and believed to be correct and current at time of publishing. The Williamson Manufacturing Company Ltd cannot accept responsibility for its inaccuracy or any errors or omissions contained herein. Copyright The Williamson Manufacturing Company Ltd 2008

150 series stepper motor driven peristaltic pump for liquids



Specification Sheet 3 (last updated Jul 2011)

HIGH TORQUE HYBRID STEPPING MOTOR SPECIFICATIONS

General specifications		Electrical specifications	
Step Angle (°)	1.8	Rated Voltage (V)	2.7
Temperature Rise (°C)	80 Max (rated current, 2 phase on)	Rated Current (A)	1.0
Ambient temperature (°C)	-20~+50		± 2.7 (25°C)
Number of Phase	2		± 4.3
Insulation Resistance	100MΩ, Min (500VDC)	Holding Torque (Kg.cm)	1.4
Insulation Class	Class B	Detent Torque (g.cm)	100
Max.radial force (N)	28 (20mm from the flange)	Rotor Inertia (g.cm ²)	14
Max.axial force (N)	10	Weight (Kg)	0.18

VOLTAGE: 24VDC, CONSTANT CURRENT: 1.0A, HALF STEP

● **Wiring Diagram:**



The Williamson Manufacturing Company Ltd provides no warranty on usage of pumps. We recommend that life tests be carried out prior to use. This information is given in good faith and believed to be correct and current at time of publishing. The Williamson Manufacturing Company Ltd cannot accept responsibility for its inaccuracy or any errors or omissions contained herein. Copyright The Williamson Manufacturing Company Ltd 2008