Advise on pumping viscous fluids



Viscous fluids flow much slower than water-like fluids for several reasons including:

- 1. The fluid is more resistant to flow than water.
- There are greater frictional forces between the wall of the tubing and a viscous fluid than water.

Peristaltic (tubing) pumps are ideal for pumping viscous fluids. To maximize the efficiency of a peristaltic pump system, follow these steps.

- 1. Slow down the speed of your pump, the fluid will only move into pump head up to a particular rate. Once this rate is achieved, increasing the motor speed will not increase flow rate. The maximum speed the system will pump efficiently decreases as viscosity increases and as tubing size decreases.
- 2. Choose a larger size tubing than what is required for pumping water. Chose approximate flow rates of various viscosity fluids at 100 rpm for different sizes of Masterflex L/Se tubing. Find the viscosity of the fluid you will be pumping, go across the graph horizontally to the flow rate you require and select the next larger size tubing. Using a larger tubing size allows you to run the pump efficiently at higher drive speeds.
- 3. Choose a firm tubing with a thick wall such as Norprene®, Viton® or Tygon®. Performance will be better because the tubing springs back into its original shape quicker after it is occluded in the pump head. This allows the liquid to be pulled into the tubing with greater force.
- 4. Select a tubing with a smooth bore. This will decrease the frictional forces. Tygon or silicone are good choices.
- Pressurize the inlet to your pump slightly [less than 15-20psi (1-1.4bar)]. This will keep the inlet tubing full and allow more efficient pumping.
- Decrease the viscosity of your fluid. Heat your fluid if possible, viscosity usually decreases with temperature.

Selecting the proper size and type of tubing for pumping viscous fluids is an inexact science. Use the above tips as a general guide, and remember experimentation is the best way to select the correct tubing for your application.

The Williamson Manufacturing Company Ltd provides no warranty on usage of pumps. We recommend that life tests be carried out prior to use. This information is given in good faith and believed to be correct at the time of publishing. The Williamson Manufacturing Company Ltd cannot accept responsibility for inaccuracy or any errors contained herein. Copyright the Williamson Manufacturing Company Ltd 2008.

Williamson Manufacturing Co Ltd Unit 2, Centenary Industrial Estate Brighton BN2 4AW

IJK

Email: sales@williamsonpumps.co.uk